

Ready-wired Pressure Switches



Applications

Our pressure switches mostly have a degree of protection IP65. This may not be adequate for all applications. Especially for commercial vehicles, mobile hydraulics, and similar applications where IP67 or IP6K9K may be required.

At SUCO any commercially-available connector system can be supplied ready-wired with a customer-specific cable length. This ensures great flexibility, and we can also supply small quantities without the need for expensive tooling.

The technical data of ready-wired pressure switch variants are substantially the same as those of the standard models. Differences in the technical data will be agreed with the customer and defined on a customer-specific drawing of the ready-wired pressure switch.

Pressure switches suitable for ready-wiring

are supplied with the switching point preset in our factory. The switching point can not be changed subsequently. It is therefore essential that the switching point is stated when the order is placed.

Pressure switch ranges suitable for ready-wiring



0263/0266
0267
0269

See pages 10 - 11
for technical data



0270/0271
0290/0291
0296/0297

See page 20 - 21
for technical data

A selection from the wide variety of plugs we can supply.



Plugs to
DIN 72585

AMP Junior/Timer

Cannon plugs

AMP Superseal

Packard plugs
(Weather Pack)

Packard plugs
(Weather Pack)

Deutsch plugs
(DT 06)

Deutsch plugs
(DT 04 - 2P)

Deutsch plugs
(DT 04 - 3P)

Further plugs and
connectors available
on request

We supply the type
and length of cable
you need